

VALUE[®]

Making Your Job More Enjoyable

2023 VALUE V1.0



VALUE[®]

VALUE Mechanical & Electrical Products CO., LTD

Add: No. 5 Third Street, East Industrial Park, Wenling, Zhejiang, China

Tel: +86-576-86191959

Fax: +86-576-86191957

Email: value@worldvalue.cn

www.worldvalue.cn

Flaring Tool

Special design for R410A system



The Outstanding Advantage of VALUE's Flaring Tool


Annular rivet connection



FAQ of copper pipe	Reason	Solutions	Result of flaring
Uneven bell mouth dimensions falls short, and cannot be normally used	Traditional flaring bar Large space between up and down clamps Excessive gap of flaring bar	Annular rivet connection Annular rivet connection makes left and right flaring bar, and will never dislocate Small space between left and right bar	Even and smooth orifice, accurate dimensions

45° Eccentricity

45° eccentricity, point contact reaming, standard dimensions, more convenient to use



Accurate Flaring

Annular Rivet Connection

- Precise of flared

45° Eccentric design

- Point contact flare, dimension standard, easy to use

Model	Tubing O.D.	Accessory	Packaging
VFT-809-I	1/4", 5/16", 3/8", 1/2", 5/8", 3/4"	/	Blow case
VFT-809-IS	1/4", 5/16", 3/8", 1/2", 5/8", 3/4"	VTC-32	Blow case

Precise Placing

