

PRODUCT SPECIFICATION



1. PRODUCT CODE BEM37067

2. DESCRIPTION 2 Core x 7/0.67 + 7/0.67 Earth (2.5mm²). P.A.C.W.
V90 Insulated and 3V90 P.V.C. Sheathed.
Flat Twin & Earth Building Cable 450/750 Volt to AS/NZS 5000.2.
Oxygen Free Copper. RoHS Compliant.
TUV AUTHORISED MARKING: TUV022085EA

3. CONSTRUCTION

3.1 CONDUCTOR: 7 strands of 0.67 mm nom. Plain Annealed Copper to AS/NZS 1125 Class 2.

Max. D.C. resistance at 20C: 7.4 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS/NZS 3808.

Nominal Diameter: 3.4 mm

Nominal Wall Thickness: 0.7 mm

3.3 CORE COLOURS: 1. RED
2. GREEN/YELLOW (in centre)
3. BLACK
Laid parallel

3.4 SHEATH: Coloured 3V90 P.V.C. to AS/NZS 3808.
Flat configuration

Nominal Dimensions: 5.5 x 12.2 mm

Nominal Wall Thickness: 1.0 mm

3.5 IDENTIFICATION: Printed on the sheath at maximum distance of 550mm:

> | < 001M TYCAB AUSTRALIA DD/MM/YYYY HH:MM V-90 ELECTRIC CABLE 450/750V
TUV-026882-EA RCM E7557 BEM37067 2.5MM² T&E

And Metre Marked

