



Air Conditioning Cable

Application: For low voltage air conditioner connections.
Conductor: Plain Annealed Copper
Sheath Colour: Blue
Standards: AS/NZS 5000.2, AS/NZS 1125, AS/NZS 3808
Greenstar: Approved
Drum Sizes: 100m

ELECTRA Part Number	SIZE	CORES	CORE Colours	INSULATION Thickness	INSULATION
AC7402	0.88	2	Red, Black	0.6	V75 PVC
AC7502	1.5	2	Red, Black	0.6	V75 PVC
AC7504	1.5	4	Red, Black, White, G/Y	0.6	V90 PVC
AC76702	2.5	2	Red, Black	0.8	V75 PVC
AC76704	2.5	4	Red, Black, White, G/Y	0.7	V90 PVC

*Size = mm², Insulation Thickness = mm.

ELECTRA Part Number	VOLTAGE	SHEATH Thickness	SHEATH	O.D.
AC7402	250/250V	0.8	V75 PVC	6.1 x 3.8
AC7502	250/250V	0.8	V75 PVC	6.7 x 4.1
AC7504	450/750V	0.9	3V-90 PVC Easytear	12.4 x 4.4
AC76702	250/250V	1.0	V75 PVC	6.7 x 4.1
AC76704	450/750V	1.0	3V-90 PVC Easytear	15.5 x 5.4

*Sheath Thickness & O.D. = mm. O.D. ± 10%

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38